



Material Safety Data Sheet

NFPA	HMIS	PPE	Transport Symbol						
	<table border="1"> <tr> <td>Health Hazard</td> <td>0</td> </tr> <tr> <td>Fire Hazard</td> <td>1</td> </tr> <tr> <td>Reactivity</td> <td>0</td> </tr> </table>	Health Hazard	0	Fire Hazard	1	Reactivity	0		
Health Hazard	0								
Fire Hazard	1								
Reactivity	0								

Issuing Date 03-May-2007

Revision Date 03-May-2007

Revision Number 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name BIC Mark-It Permanent Marker (All colors)

Recommended Use Marking Instrument

Supplier Address

BIC USA Inc.
500 BIC Drive
Milford, CT 06460
Phone Number: 203 783-2000

Company Emergency Phone Number 203-783-2412

2. HAZARDS IDENTIFICATION

Appearance Varies

Physical State Solid

Odor Alcohol

OSHA Regulatory Status

Information listed in Sections 3,11, and 15 is consistent with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and has also been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR). This product is not a toxic or hazardous substance as defined by CFR 1500.3 of the Federal Hazardous Substances Act (FSHSA) and as such does not require acute or chronic hazard labeling. The ink in this writing instrument has been approved by board certified toxicologists under the WIMA (Writing Instrument Manufacturer's Association) certification program and/or the ACMI (Art & Creative Materials Institute) certification programs. Reviews were conducted using guidelines set forth by the CPSC (Consumer Product Safety Commission). Inks are certified as compliant under ASTM D-4236.

Potential Health Effects

Principle Routes of Exposure

Potential exposure to ink by inhalation, skin contact, eye contact.

Acute Toxicity	
Eyes	Ink may cause slight irritation.
Skin	None known.
Inhalation	No known hazard by inhalation.
Ingestion	Ingestion of ink may cause stomach discomfort.
Chronic Effects	None known
Aggravated Medical Conditions	None known
Environmental Hazard	None known

3. COMPOSITION/INFORMATION ON INGREDIENTS

The following represents the ink component of an entire line of products. Each individual ink may not contain all the ingredients listed below. In addition to the items listed below, the products also contain various dyes.

Chemical Name	CAS-No
Propylene glycol monomethyl ether	107-98-2
Diacetone alcohol	123-42-2
3-Methoxybutanol	2517-43-3
C.I. Solvent Violet 9	467-63-0
Ethyl alcohol	64-17-5
n-Propyl alcohol	71-23-8
2-butoxyethanol	111-76-2

4. FIRST AID MEASURES

Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.
Skin Contact	Wash skin with soap and water.
Inhalation	Move victim to fresh air.
Ingestion	Clean mouth with water and afterwards drink plenty of water. If symptoms persist, call a physician. Do not induce vomiting without medical advice.
Notes to Physician	Treat symptomatically

5. FIRE-FIGHTING MEASURES

Flammable Properties	The ink is a flammable/combustible material.
Flash Point	13°C / 55.4°F (Liquid Ink)
Suitable Extinguishing Media	Dry chemical, CO ₂ , water spray or regular foam. Water spray, fog or regular foam. Use water spray or fog; do not use straight streams. Move containers from fire area if you can do it without risk.
Explosion Data	
Sensitivity to mechanical impact	None
Sensitivity to static discharge	None

Protective Equipment and Precautions for Firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

NFPA	Health Hazard 0	Flammability 1	Stability 0	Physical and Chemical Hazards -
HMS	Health Hazard 0	Flammability 1	Stability 0	Personal Precautions -

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Remove all sources of ignition.
Methods for Containment	Not applicable.
Methods for Cleaning Up	Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Handling	No special requirements for writing instruments.
Storage	No special requirements for writing instruments.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines The following exposure limits are provided for information only; exposure is not expected under normal conditions of use or storage.

Chemical Name	ACGIH TLV	OSHA PEL
Propylene glycol monomethyl ether	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm
Diacetone alcohol	TWA: 50 ppm	TWA: 240 mg/m ³
Ethyl alcohol	TWA: 1000 ppm	TWA: 1000 ppm
n-Propyl alcohol	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm

Engineering Measures	None under normal use conditions.
Personal Protective Equipment	
Eye/Face Protection	None under normal use conditions.
Skin and Body protection	None under normal use conditions.
Respiratory Protection	None under normal use conditions.
Hygiene Measures	None under normal use conditions.