

UHU

Technical Data Sheet

UHU tac



UHU tac lets you stick pieces of paper or small objects to most materials and surfaces, including wood, plaster, glass, metal, plastic, china and much more. 1000's of uses all around the home, office and school.

UHU tac is made from a kneadable caoutchouc compound. The product is characterised by very high levels of adhesion. White silicon-treated masking paper provides the UHU tac compound with protection and the upper side is protected by a transparent plastic film.

Specification:	Appearance:	Strips of adhesive pads
	Consistency:	Solid
	Basis:	Modified polybutene caoutchouc
	Covering:	Silicon-treated paper, film
	Identification in acc. with harmful substance ruling:	None

Properties:

UHU tac is a self-adhesive fastening system based on a modified polybutene caoutchouc. It is available in white.

Examples of application:

Suitable for fixing of posters, decorations, phones, cables and much more.

Usage:

The areas to be glued must be dry and free of any dust or grease. A gentle tug will release the UHU tac adhesive pads and the masking paper can be easily removed. Then pull off the size of pad required and knead until the compound is soft. Stick UHU tac to the object to be secured and fix to the position required by pushing on firmly.

Cleaning:

To remove, pull off adhesive pads. Any remaining adhesive should be removed by rubbing off or dabbing with the adhesive pad removed. Any flecks remaining should be cleaned with petroleum ether.

Precautionary measures:

Not suitable for delicate surfaces. Do not use on recently painted areas and wallpaper. Keep away from children: danger of confusion with chewing gum.

Storage properties:

Products can be stored for at least 2 years at a temperature between 15°C and 25°C and at 50% relative humidity.

Package size: cube Net Wt. 3 oz./85, wallet containing 80 glue pads, wallet containing 160 pads

UHU

Technical Data Sheet

UHU tac



Note:

This information is the result of carefully executed tests. This Technical Data Sheet has been prepared to the best of our knowledge to provide you with advice when gluing. We cannot be held responsible for the results or any damage suffered, as the variety of factors involved (type and combination of materials and working method) are beyond our control. Users have to carry out their own checks and trials. Liability can only be accepted for the consistently high quality of our product.